

PRODUCT-DETAILS

3GGP131324-BDB

M3GP 132SMC 2



General Information

Product ID	3GGP131324-BDB
ABB Type Designation	M3GP 132SMC 2
Catalog Description	M3GP 132SMC 2

Additional Information

ABB Type Designation	M3GP 132SMC 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	7.50 kW	2890 r/min	8.30 A	0.890	88.20 %	24.90 N-m	7.30
D	T3	50 Hz	400 V	7.50 kW	2890 r/min	13.70 A	0.890	88.20 %	24.90 N-m	7.30
D	T3	60 Hz	460 V	7.50 kW	3505 r/min	12.10 A	0.880	89.50 %	20.48 N-m	8.30

Gas Group	IIC
Gross Weight	75 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 88.2 % Partial Load (75%) 88.8 % Partial Load (50%) 87.6 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 89.5 % Partial Load (75%) 89.1 % Partial Load (50%) 86.8 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 132SMC 2
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	70 kg
Product Type	3GP0__M3GP_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

