

PRODUCT-DETAILS

3GGP132250-ADL

M3GP 132SME 4



General Information

Product ID	3GGP132250-ADL
ABB Type Designation	M3GP 132SME 4
Catalog Description	M3GP 132SME 4

Additional Information

ABB Type Designation	M3GP 132SME 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	7.50 kW	1462 r/min	9.00 A	0.760	90.40 %	49.00 N-m	7.90
D	T3	50 Hz	400 V	7.50 kW	1462 r/min	15.70 A	0.760	90.40 %	49.00 N-m	7.90
D	T3	50 Hz	415 V	7.50 kW	1464 r/min	16.50 A	0.700	90.40 %	49.00 N-m	8.30

Gas Group	IIC
Gross Weight	83 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 90.4 % Partial Load (75%) 90.5 % Partial Load (50%) 89.3 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 89.5 % Partial Load (75%) 89.2 % Partial Load (50%) 87.5 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 132SME 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	78 kg
Product Type	5GP3 M3GP CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors



