

PRODUCT-DETAILS

3GGP132323-ASB

M3GP 132SMC 4



General Information

Product ID	3GGP132323-ASB
ABB Type Designation	M3GP 132SMC 4
Catalog Description	M3GP 132SMC 4

Additional Information

ABB Type Designation	M3GP 132SMC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	7.50 kW	1450 r/min	14.50 A	0.810	89.30 %	49.40 N-m	7.20
D	T3	50 Hz	230 V	7.50 kW	1450 r/min	25.20 A	0.810	89.30 %	49.40 N-m	7.20
Y	T3	60 Hz	460 V	7.50 kW	1760 r/min	12.70 A	0.820	90.50 %	40.88 N-m	8.20

Gas Group	IIC
Gross Weight	78 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 89.3 % Partial Load (75%) 90.1 % Partial Load (50%) 90.0 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 90.5 % Partial Load (75%) 90.4 % Partial Load (50%) 88.8 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 132SMC 4
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	73 kg
Product Type	3GP0__M3GP_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class	T3
Default	
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors



