

PRODUCT-DETAILS

3GGP133220-ASL

M3GP 132SMB 6



General Information

Product ID	3GGP133220-ASL
ABB Type Designation	M3GP 132SMB 6
Catalog Description	M3GP 132SMB 6

Additional Information

ABB Type Designation	M3GP 132SMB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	3.00 kW	973 r/min	8.00 A	0.620	85.60 %	29.20 N·m	6.60
D	T3	50 Hz	230 V	3.00 kW	973 r/min	14.00 A	0.620	85.60 %	29.20 N·m	6.60
Y	T3	50 Hz	415 V	3.00 kW	974 r/min	8.10 A	0.590	85.60 %	29.20 N·m	6.80

Gas Group	IIC
Gross Weight	80 kg

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 85.6 % Partial Load (75%) 84.9 % Partial Load (50%) 82.3 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 87.5 % Partial Load (75%) 86.5 % Partial Load (50%) 83.9 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 132SMB 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	75 kg
Product Type	5GP3 M3GP CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors



