

PRODUCT-DETAILS

3GGP134210-BFK

No Description Available



General Information

Product ID	3GGP134210-BFK
ABB Type Designation	M3GP 132SMA 8
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3GP 132SMA 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	500 V	2.20 kW	725 r/min	4.64 A	0.640	81.90 %	28.90 N·m	5.20
Y	T3	60 Hz	575 V	2.20 kW	879 r/min	4.16 A	0.600	85.50 %	23.90 N·m	5.70

Gas Group	IIC
Gross Weight	71 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 81.9 % Partial Load (75%) 82.3 % Partial Load (50%) 80.2 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 85.5 % Partial Load (75%) 84.9 % Partial Load (50%) 82.2 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	66 kg
Product Type	3GP3_M3GP_IE3_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	F
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

