

PRODUCT-DETAILS

3GGP134290-CDL

M3GP 132SMJ 8



General Information

Product ID	3GGP134290-CDL
ABB Type Designation	M3GP 132SMJ 8
Catalog Description	M3GP 132SMJ 8

Additional Information

ABB Type Designation	M3GP 132SMJ 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	3.00 kW	716 r/min	4.50 A	0.650	83.50 %	40.00 N·m	4.40
D	T3	50 Hz	400 V	3.00 kW	716 r/min	7.90 A	0.650	83.50 %	40.00 N·m	4.40
D	T3	50 Hz	415 V	3.00 kW	720 r/min	7.80 A	0.630	83.50 %	40.00 N·m	4.60

Gas Group	IIC
Gross Weight	88 kg

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 83.5 % Partial Load (75%) 84.0 % Partial Load (50%) 82.7 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 86.5 % Partial Load (75%) 86.5 % Partial Load (50%) 84.9 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 132SMJ 8
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GGP134290-BDL
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	83 kg
Product Type	5GP3 M3GP CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	T3
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors



