

PRODUCT-DETAILS

3GGP161410-BDK

M3GP 160MLA 2



General Information

Product ID	3GGP161410-BDK
ABB Type Designation	M3GP 160MLA 2
Catalog Description	M3GP 160MLA 2

Additional Information

ABB Type Designation	M3GP 160MLA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309/C3
Bearing NDE	6209/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	11.00 kW	2943 r/min	10.80 A	0.920	92.10 %	35.60 N·m	8.10
D	T3	50 Hz	400 V	11.00 kW	2943 r/min	18.70 A	0.920	92.10 %	35.60 N·m	8.10
Y	T3	50 Hz	660 V	11.00 kW	2934 r/min	11.40 A	0.930	91.50 %	35.60 N·m	7.40
D	T3	50 Hz	380 V	11.00 kW	2934 r/min	19.60 A	0.930	91.50 %	35.60 N·m	7.40
D	T3	50 Hz	415 V	11.00 kW	2948 r/min	18.20 A	0.910	92.20 %	35.60 N·m	8.70
D	T3	60 Hz	460 V	11.00 kW	3552 r/min	16.50 A	0.910	91.80 %	29.50 N·m	9.20

Gas Group	IIC
Gross Weight	151 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 91.5 % Partial Load (75%) 92.5 % Partial Load (50%) 92.5 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 91.8 % Partial Load (75%) 91.8 % Partial Load (50%) 90.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 160MLA 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	141 kg
Product Type	3GP3_M3GP_IE3_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class	T3
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

