

PRODUCT-DETAILS

3GGP161430-BDK

M3GP 160MLC 2



General Information

Product ID	3GGP161430-BDK
ABB Type Designation	M3GP 160MLC 2
Catalog Description	M3GP 160MLC 2

Additional Information

ABB Type Designation	M3GP 160MLC 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309/C3
Bearing NDE	6209/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	18.50 kW	2942 r/min	17.90 A	0.930	93.10 %	60.00 N-m	8.30
D	T3	50 Hz	400 V	18.50 kW	2942 r/min	30.80 A	0.930	93.10 %	60.00 N-m	8.30
Y	T3	50 Hz	660 V	18.50 kW	2935 r/min	18.90 A	0.930	92.70 %	60.00 N-m	7.40
D	T3	50 Hz	380 V	18.50 kW	2935 r/min	32.60 A	0.930	92.70 %	60.00 N-m	7.40
D	T3	50 Hz	415 V	18.50 kW	2948 r/min	30.00 A	0.920	93.20 %	60.00 N-m	8.90
D	T3	60 Hz	460 V	18.50 kW	3551 r/min	26.80 A	0.930	92.90 %	49.70 N-m	9.50

Gas Group	IIC
Gross Weight	193 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 92.7 % Partial Load (75%) 93.7 % Partial Load (50%) 94.0 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 92.9 % Partial Load (75%) 93.1 % Partial Load (50%) 92.4 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 160MLC 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	183 kg
Product Type	3GP3_M3GP_IE3_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class	T3
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

