

PRODUCT-DETAILS

3GGP161440-BDD

M3GP 160MLD 2



General Information

Product ID	3GGP161440-BDD
ABB Type Designation	M3GP 160MLD 2
Catalog Description	M3GP 160MLD 2

Additional Information

ABB Type Designation	M3GP 160MLD 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309/C3
Bearing NDE	6209/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	22.00 kW	2929 r/min	22.20 A	0.900	91.20 %	71.70 N·m	7.50
D	T3	50 Hz	400 V	22.00 kW	2929 r/min	38.30 A	0.900	91.20 %	71.70 N·m	7.50
D	T3	50 Hz	415 V	22.00 kW	2935 r/min	37.70 A	0.890	91.20 %	71.56 N·m	8.10

Gas Group	IIC
Gross Weight	176 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 91.2 % Partial Load (75%) 91.5 % Partial Load (50%) 90.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 160MLD 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	166 kg
Product Type	3GP0__M3GP_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	T3
Default	
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

