

PRODUCT-DETAILS

3GGP162470-ASH

HIGH OUTPUT



General Information

Product ID	3GGP162470-ASH
ABB Type Designation	M3GP 160MLG 4
Catalog Description	HIGH OUTPUT

Additional Information

ABB Type Designation	M3GP 160MLG 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309/C3
Bearing NDE	6309/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	22.00 kW	1466 r/min	43.90 A	0.810	90.80 %	143.30 N·m	8.20
D	T3	50 Hz	230 V	22.00 kW	1466 r/min	75.50 A	0.810	90.80 %	143.40 N·m	8.20
Y	T3	50 Hz	415 V	22.00 kW	1469 r/min	43.90 A	0.780	90.80 %	143.04 N·m	8.70

Gas Group	IIC
Gross Weight	259 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1
	Full Load (100%) 90.8 %
	Partial Load (75%) 90.9 %
	Partial Load (50%) 90.0 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	HIGH OUTPUT
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	249 kg
Product Type	3GP2__M3GP_IE2_CI
Quote Only	No
Replaced Product ID (OLD)	3GGP162470-ASG
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors



