

PRODUCT-DETAILS

3GGP181420-AED

M3GP 180MLB 2



General Information

Product ID	3GGP181420-AED
ABB Type Designation	M3GP 180MLB 2
Catalog Description	M3GP 180MLB 2

Additional Information

ABB Type Designation	M3GP 180MLB 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6310/C3
Bearing NDE	6209/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	T3	50 Hz	500 V	30.00 kW	2942 r/min	41.80 A	0.900	92.50 %	97.30 N-m	7.00

Gas Group	IIC
Gross Weight	246 kg
IC Class	IC411

IE Class Data (50 Hz)

IE Class IE2
Full Load (100%) 92.5 %
Partial Load (75%) 93.2 %
Partial Load (50%) 92.6 %

IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 180MLB 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	236 kg
Product Type	3GP0__M3GP_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE2 LV motors

