

PRODUCT-DETAILS

3GGP201420-ASK

M3GP 200MLB 2



General Information

Product ID	3GGP201420-ASK
ABB Type Designation	M3GP 200MLB 2
Catalog Description	M3GP 200MLB 2

Additional Information

ABB Type Designation	M3GP 200MLB 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312/C3
Bearing NDE	6210/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	37.00 kW	2960 r/min	65.50 A	0.860	94.70 %	119.00 N-m	8.80
D	T3	50 Hz	230 V	37.00 kW	2960 r/min	114.00 A	0.860	94.70 %	119.00 N-m	8.80
Y	T3	50 Hz	380 V	37.00 kW	2955 r/min	68.60 A	0.870	94.20 %	119.00 N-m	7.90
D	T3	50 Hz	220 V	37.00 kW	2955 r/min	119.00 A	0.870	94.20 %	119.00 N-m	7.90
Y	T3	50 Hz	415 V	37.00 kW	2964 r/min	63.20 A	0.860	94.60 %	119.00 N-m	9.40
Y	T3	60 Hz	460 V	37.00 kW	3566 r/min	54.00 A	0.910	94.00 %	99.00 N-m	10.00

Gas Group	IIC
Gross Weight	324 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 94.2 % Partial Load (75%) 94.9 % Partial Load (50%) 94.9 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 94.0 % Partial Load (75%) 94.1 % Partial Load (50%) 93.3 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 200MLB 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	314 kg
Product Type	3GP3_M3GP_IE3_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class	T3
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

