

PRODUCT-DETAILS

3GGP201420-CDL

M3GP 200MLB 2



General Information

Product ID	3GGP201420-CDL
ABB Type Designation	M3GP 200MLB 2
Catalog Description	M3GP 200MLB 2

Additional Information

ABB Type Designation	M3GP 200MLB 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312/C3
Bearing NDE	6210/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	37.00 kW	2960 r/min	37.00 A	0.890	93.70 %	119.50 N·m	8.20
D	T3	50 Hz	400 V	37.00 kW	2960 r/min	64.20 A	0.890	93.70 %	119.50 N·m	8.20
D	T3	50 Hz	415 V	37.00 kW	2963 r/min	62.10 A	0.880	93.70 %	119.37 N·m	8.80

Gas Group	IIC
Gross Weight	299 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 93.7 % Partial Load (75%) 94.1 % Partial Load (50%) 93.9 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 93.0 % Partial Load (75%) 93.0 % Partial Load (50%) 92.0 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 200MLB 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	289 kg
Product Type	5GP3 M3GP CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors



