


PRODUCT-DETAILS

3GGP202450-ADK

M3GP 200MLE 4

For sale but "Obsolete", replaced by



General Information

Product ID	3GGP202450-ADK
ABB Type Designation	M3GP 200MLE 4
Catalog Description	M3GP 200MLE 4

Additional Information

ABB Type Designation	M3GP 200MLE 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312/C3
Bearing NDE	6210/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed
D	T3	50 Hz	400 V	30.00 kW	1500 r/min
Y	T3	50 Hz	690 V	30.00 kW	1500 r/min
D	T3	50 Hz	415 V	30.00 kW	1500 r/min

Gas Group	IIC
Gross Weight	327 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3

	Full Load (100%) 93.7 % Partial Load (75%) 94.5 % Partial Load (50%) 94.4 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 200MLE 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	317 kg
Product Type	3GP3__M3GP_IE3_CI
Quote Only	No
Replacement Product ID (NEW)	3GGP202410-ADK
Selling Unit of Measure	piece
Temperature Class Default	T3
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

