

PRODUCT-DETAILS

3GGP203410-BEG

M3GP 200MLA 6



General Information

Product ID	3GGP203410-BEG
ABB Type Designation	M3GP 200MLA 6
Catalog Description	M3GP 200MLA 6

Additional Information

ABB Type Designation	M3GP 200MLA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312/C3
Bearing NDE	6310/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	T3	50 Hz	500 V	18.50 kW	983 r/min	28.70 A	0.820	90.60 %	179.00 N·m	6.40
D	T3	60 Hz	575 V	18.50 kW	1185 r/min	25.20 A	0.810	91.00 %	148.00 N·m	7.50

Gross Weight	310 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 90.0 % Partial Load (75%) 91.0 % Partial Load (50%) 90.0 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 91.0 % Partial Load (75%) 90.9 % Partial Load (50%) 89.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 200MLA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Output Power	18.50 kW
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	300 kg
Product Type	3GP2__M3GP_IE2_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	T3
Default	
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators
→ Motors and Generators for Explosive Atmospheres
→ Dust Ignition Proof Motors
→ Dust Ignition Proof IE2 LV motors

Motors and Generators
→ Motors and Generators for Explosive Atmospheres
→ Increased Safety Ex ec Zone 2 Motors
→ Increased Safety IE2 Ex ec Motors



