

PRODUCT-DETAILS

3GGP222220-BSK

M3GP 225SMB 4



General Information

Product ID	3GGP222220-BSK
ABB Type Designation	M3GP 225SMB 4
Catalog Description	M3GP 225SMB 4

Additional Information

ABB Type Designation	M3GP 225SMB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6313/C3
Bearing NDE	6212/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	45.00 kW	1482 r/min	80.20 A	0.850	95.20 %	289.00 N-m	7.90
D	T3	50 Hz	230 V	45.00 kW	1482 r/min	140.00 A	0.850	95.20 %	289.00 N-m	7.90
Y	T3	50 Hz	380 V	45.00 kW	1479 r/min	83.90 A	0.860	94.60 %	289.00 N-m	7.20
D	T3	50 Hz	220 V	45.00 kW	1479 r/min	145.00 A	0.860	94.60 %	289.00 N-m	7.20
Y	T3	50 Hz	415 V	45.00 kW	1483 r/min	78.30 A	0.840	95.10 %	289.00 N-m	8.50
Y	T3	60 Hz	460 V	45.00 kW	1785 r/min	70.50 A	0.840	95.30 %	240.00 N-m	8.90

Gas Group	IIC
Gross Weight	408 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 94.6 % Partial Load (75%) 95.4 % Partial Load (50%) 95.5 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 95.3 % Partial Load (75%) 95.4 % Partial Load (50%) 94.8 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 225SMB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	398 kg
Product Type	3GP3_M3GP_IE3_CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class	T3
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

