

PRODUCT-DETAILS

3GGP222220-BSL

M3GP 225SMB 4



General Information

Product ID	3GGP222220-BSL
ABB Type Designation	M3GP 225SMB 4
Catalog Description	M3GP 225SMB 4

Additional Information

ABB Type Designation	M3GP 225SMB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6313/C3
Bearing NDE	6212/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	45.00 kW	1482 r/min	82.30 A	0.840	94.20 %	290.00 N-m	8.00
D	T3	50 Hz	230 V	45.00 kW	1482 r/min	143.00 A	0.840	94.20 %	290.00 N-m	8.00
Y	T3	50 Hz	415 V	45.00 kW	1483 r/min	81.00 A	0.820	94.20 %	290.00 N-m	8.60
Y	T3	60 Hz	440 V	45.00 kW	1782 r/min	73.40 A	0.850	95.00 %	241.20 N-m	8.10
Y	T3	60 Hz	460 V	45.00 kW	1784 r/min	71.80 A	0.830	95.00 %	241.20 N-m	8.80

Gas Group	IIC
Gross Weight	367 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 94.2 % Partial Load (75%) 94.3 % Partial Load (50%) 93.8 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 95.0 % Partial Load (75%) 94.9 % Partial Load (50%) 95.0 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 225SMB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	357 kg
Product Type	5GP3 M3GP CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class	T3
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

