


PRODUCT-DETAILS

3GGP222260-BDK

M3GP 225SMF 4

For sale but "Obsolete", replaced by



General Information

Product ID	3GGP222260-BDK
ABB Type Designation	M3GP 225SMF 4
Catalog Description	M3GP 225SMF 4

Additional Information

ABB Type Designation	M3GP 225SMF 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6313/C3
Bearing NDE	6212/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015290
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed
D	T3	50 Hz	400 V	45.00 kW	1500 r/min
Y	T3	50 Hz	690 V	45.00 kW	1500 r/min
D	T3	50 Hz	415 V	45.00 kW	1500 r/min

Gas Group	IIC
Gross Weight	420 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3

	Full Load (100%) 94.8 % Partial Load (75%) 95.2 % Partial Load (50%) 95.0 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 225SMF 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	410 kg
Product Type	3GP3__M3GP_IE3_CI
Quote Only	No
Replacement Product ID (NEW)	3GGP222220-BDK
Selling Unit of Measure	piece
Temperature Class Default	T3
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

