

PRODUCT-DETAILS

3GGP223210-ADK

M3GP 225SMA 6



General Information

Product ID	3GGP223210-ADK
ABB Type Designation	M3GP 225SMA 6
Catalog Description	M3GP 225SMA 6

Additional Information

ABB Type Designation	M3GP 225SMA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6313/C3
Bearing NDE	6212/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	30.00 kW	989 r/min	32.90 A	0.810	92.90 %	289.00 N-m	7.90
D	T3	50 Hz	400 V	30.00 kW	989 r/min	56.80 A	0.810	92.90 %	289.00 N-m	7.90
Y	T3	50 Hz	660 V	30.00 kW	987 r/min	33.70 A	0.830	92.90 %	289.00 N-m	7.30
D	T3	50 Hz	380 V	30.00 kW	987 r/min	58.50 A	0.830	92.90 %	289.00 N-m	7.30
D	T3	50 Hz	415 V	30.00 kW	990 r/min	56.00 A	0.790	92.90 %	289.00 N-m	8.40
D	T3	60 Hz	460 V	30.00 kW	1191 r/min	49.90 A	0.800	94.10 %	240.00 N-m	8.90

Gas Group	IIC
Gross Weight	402 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 92.9 % Partial Load (75%) 93.3 % Partial Load (50%) 92.9 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 94.1 % Partial Load (75%) 94.2 % Partial Load (50%) 93.4 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 225SMA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	392 kg
Product Type	3GP3_M3GP_IE3_CI
Quote Only	No
Replaced Product ID (OLD)	3GGP223250-ADK
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	T3
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

