

PRODUCT-DETAILS

3GGP224210-BSK

No Description Available



General Information

Product ID	3GGP224210-BSK
ABB Type Designation	M3GP 225SMA 8
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3GP 225SMA 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6313/C3
Bearing NDE	6212/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	18.50 kW	736 r/min	39.80 A	0.740	90.10 %	240.00 N·m	5.20
D	T3	50 Hz	230 V	18.50 kW	736 r/min	69.00 A	0.740	90.10 %	240.00 N·m	5.20
Y	T3	50 Hz	380 V	18.50 kW	735 r/min	41.20 A	0.750	90.10 %	240.00 N·m	4.70
D	T3	50 Hz	220 V	18.50 kW	735 r/min	71.40 A	0.750	90.10 %	240.00 N·m	4.70
Y	T3	50 Hz	415 V	18.50 kW	737 r/min	39.20 A	0.720	90.10 %	240.00 N·m	5.60
Y	T3	60 Hz	460 V	18.50 kW	890 r/min	35.10 A	0.720	90.20 %	198.00 N·m	5.90

Gas Group	IIC
Gross Weight	360 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 90.1 % Partial Load (75%) 90.4 % Partial Load (50%) 89.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 90.2 % Partial Load (75%) 90.3 % Partial Load (50%) 89.0 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	350 kg
Product Type	3GP3__M3GP_IE3_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

