

PRODUCT-DETAILS

3GGP251210-BSL

M3GP 250SMA 2



General Information

Product ID	3GGP251210-BSL
ABB Type Designation	M3GP 250SMA 2
Catalog Description	M3GP 250SMA 2

Additional Information

ABB Type Designation	M3GP 250SMA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6315/C3
Bearing NDE	6213/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	400 V	55.00 kW	2968 r/min	94.80 A	0.890	94.30 %	177.00 N·m	6.80
D	T3	50 Hz	230 V	55.00 kW	2968 r/min	164.00 A	0.890	94.30 %	177.00 N·m	6.80
Y	T3	50 Hz	415 V	55.00 kW	2970 r/min	92.10 A	0.890	94.30 %	177.00 N·m	7.30
Y	T3	60 Hz	440 V	55.00 kW	3566 r/min	85.90 A	0.890	93.60 %	147.00 N·m	7.20
Y	T3	60 Hz	460 V	55.00 kW	3569 r/min	82.70 A	0.900	93.60 %	147.00 N·m	7.90

Gas Group	IIC
Gross Weight	410 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 94.3 % Partial Load (75%) 93.6 % Partial Load (50%) 93.3 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 93.6 % Partial Load (75%) 93.1 % Partial Load (50%) 91.7 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 250SMA 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	400 kg
Product Type	5GP3 M3GP CI
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	T3
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

