

PRODUCT-DETAILS

3GGP254210-BDK

No Description Available



General Information

Product ID	3GGP254210-BDK
ABB Type Designation	M3GP 250SMA 8
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3GP 250SMA 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6315/C3
Bearing NDE	6213/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	30.00 kW	741 r/min	38.60 A	0.710	91.30 %	386.00 N-m	5.60
D	T3	50 Hz	400 V	30.00 kW	741 r/min	67.00 A	0.710	91.30 %	386.00 N-m	5.60
Y	T3	50 Hz	660 V	30.00 kW	740 r/min	39.60 A	0.730	91.30 %	387.00 N-m	5.10
D	T3	50 Hz	380 V	30.00 kW	740 r/min	68.60 A	0.730	91.30 %	387.00 N-m	5.10
D	T3	50 Hz	415 V	30.00 kW	742 r/min	66.60 A	0.680	91.30 %	386.00 N-m	5.90
D	T3	60 Hz	460 V	30.00 kW	892 r/min	59.40 A	0.680	91.70 %	321.00 N-m	6.30

Gas Group	IIC
Gross Weight	450 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 91.3 % Partial Load (75%) 91.1 % Partial Load (50%) 89.7 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 91.7 % Partial Load (75%) 91.8 % Partial Load (50%) 90.5 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	440 kg
Product Type	3GP3__M3GP_IE3_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	T3
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

