


PRODUCT-DETAILS

3GGP284220-ADL

M3GP 280SMB 8



General Information

Product ID	3GGP284220-ADL
ABB Type Designation	M3GP 280SMB 8
Catalog Description	M3GP 280SMB 8

Additional Information

ABB Type Designation	M3GP 280SMB 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T3	50 Hz	690 V	45.00 kW	741 r/min	51.70 A	0.780	92.20 %	579.00 N·m	7.60
D	T3	50 Hz	400 V	45.00 kW	741 r/min	89.60 A	0.780	92.20 %	579.00 N·m	7.60
D	T3	50 Hz	415 V	45.00 kW	742 r/min	88.30 A	0.760	92.20 %	579.00 N·m	8.00

Gas Group	IIC
Gross Weight	665 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 92.2 % Partial Load (75%) 92.1 % Partial Load (50%) 90.9 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 92.4 % Partial Load (75%) 92.1 % Partial Load (50%) 90.6 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 280SMB 8
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	645 kg
Product Type	5GP3 M3GP CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T3
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

