

PRODUCT-DETAILS

3GGP312820-AEK

M3GP 315LKB 4



General Information

Product ID	3GGP312820-AEK
ABB Type Designation	M3GP 315LKB 4
Catalog Description	M3GP 315LKB 4

Additional Information

ABB Type Designation	M3GP 315LKB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6319/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
EX-Protection	Exec

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	T3	50 Hz	500 V	200.00 kW	1490 r/min	278.00 A	0.870	96.60 %	1280.00 N·m	7.60
D	T3	60 Hz	575 V	200.00 kW	1791 r/min	241.00 A	0.860	96.40 %	1066.00 N·m	8.70

Gross Weight	1500 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 96.6 % Partial Load (75%) 96.8 % Partial Load (50%) 96.7 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 96.4 % Partial Load (75%) 96.4 % Partial Load (50%) 95.9 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3GP 315LKB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1480 kg
Product Type	3GP3_M3GP_IE3_CI
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	T3
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors



