

PRODUCT-DETAILS

# 3GGP401520-ADK

No Description Available



## General Information

|                      |                          |
|----------------------|--------------------------|
| Product ID           | 3GGP401520-ADK           |
| ABB Type Designation | M3GP 400LB 2             |
| Catalog Description  | No Description Available |

## Additional Information

|                       |              |
|-----------------------|--------------|
| ABB Type Designation  | M3GP 400LB 2 |
| Altitude              | 1000 m       |
| Ambient Temperature   | 40 °C        |
| Bearing               | 6317M/C3     |
| Bearing NDE           | 6317M/C3     |
| Country of Origin     | Finland (FI) |
| Customs Tariff Number | 85015394     |
| Direction of Rotation | CW Clockwise |
| EX-Protection         | Exec         |
| Electrical Data       |              |

| Conn | Temp Class | Freq  | Voltage | Power     | Speed      | Current   | Power Factor | Efficiency | Torque      | IS/IN |
|------|------------|-------|---------|-----------|------------|-----------|--------------|------------|-------------|-------|
| Y    | T3         | 50 Hz | 690 V   | 630.00 kW | 2987 r/min | 611.00 A  | 0.890        | 95.80 %    | 2014.00 N·m | 7.60  |
| D    | T3         | 50 Hz | 400 V   | 630.00 kW | 2987 r/min | 1049.00 A | 0.890        | 95.80 %    | 2014.00 N·m | 7.60  |
| D    | T3         | 50 Hz | 415 V   | 630.00 kW | 2987 r/min | 1024.00 A | 0.880        | 95.80 %    | 2014.00 N·m | 8.10  |
| D    | T3         | 60 Hz | 460 V   | 630.00 kW | 3588 r/min | 916.00 A  | 0.890        | 95.80 %    | 1676.00 N·m | 8.60  |

|                         |                                                                                                   |
|-------------------------|---------------------------------------------------------------------------------------------------|
| Gas Group               | IIC                                                                                               |
| Gross Weight            | 3090 kg                                                                                           |
| IC Class                | IC411                                                                                             |
| IE Class Data (50 Hz)   | IE Class IE3<br>Full Load (100%) 95.8 %<br>Partial Load (75%) 95.5 %<br>Partial Load (50%) 94.8 % |
| IE Class Data (60 Hz)   | IE Class IE3<br>Full Load (100%) 95.8 %<br>Partial Load (75%) 95.7 %<br>Partial Load (50%) 95.5 % |
| IM Class                | IMB3 IM1001                                                                                       |
| IP Class                | IP55                                                                                              |
| Insulation Class        | ICLF                                                                                              |
| Made To Order           | No                                                                                                |
| Minimum Order Quantity  | 1 piece                                                                                           |
| Number of Poles (High)  | 2                                                                                                 |
| Order Multiple          | 1 piece                                                                                           |
| Package Level 1 Units   | 0 pallet (lift)                                                                                   |
| Product Name            | 3-Phase squirrel cage motor                                                                       |
| Product Net Weight      | 3050 kg                                                                                           |
| Product Type            | 3GP3__M3GP_IE3_CI                                                                                 |
| Quote Only              | No                                                                                                |
| Selling Unit of Measure | piece                                                                                             |
| Temperature Class       | T3                                                                                                |
| Default                 |                                                                                                   |
| Terminator Box Location | Top                                                                                               |
| Two Speed Motor         | No                                                                                                |
| Type of Duty            | S1                                                                                                |
| UNSPSC                  | 26101100                                                                                          |
| Voltage Code            | D                                                                                                 |
| WEEE Category           | 4. Large Equipment (Any External Dimension More Than 50 cm)                                       |

## Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Dust Ignition Proof Motors → Dust Ignition Proof IE3 LV Motors

