

PRODUCT-DETAILS

3GJM081320-ADJ

No Description Available



General Information

Product ID	3GJM081320-ADJ
ABB Type Designation	M3JM 80MB 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 80MB 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	0.75 kW	2895 r/min	1.04 A	0.740	79.90 %	2.40 N·m	7.70
D	--	50 Hz	400 V	0.75 kW	2895 r/min	1.80 A	0.740	79.90 %	2.40 N·m	7.70
D	--	60 Hz	460 V	0.75 kW	3510 r/min	1.62 A	0.720	78.80 %	2.04 N·m	9.10

Gross Weight	49 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 79.9 % Partial Load (75%) 78.8 % Partial Load (50%) 74.7 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 78.8 % Partial Load (75%) 76.7 % Partial Load (50%) 71.6 %
IM Class	IMB3 IM1001
IP Class	IP66
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	46 kg
Product Type	3JM0__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Replaced Product ID (OLD)	3GJM081310-ADH
Selling Unit of Measure	piece
Temperature Class	--
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

