

PRODUCT-DETAILS

3GJM081340-BEK

M3JM 80MD 2



General Information

Product ID	3GJM081340-BEK
ABB Type Designation	M3JM 80MD 2
Catalog Description	M3JM 80MD 2

Additional Information

ABB Type Designation	M3JM 80MD 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	500 V	0.75 kW	2872 r/min	1.21 A	0.870	80.70 %	2.43 N·m	6.20
D	--	60 Hz	575 V	0.75 kW	3487 r/min	1.06 A	0.860	77.00 %	2.00 N·m	7.40

Gross Weight	52 kg
--------------	-------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 80.7 % Partial Load (75%) 81.1 % Partial Load (50%) 79.4 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 77.0 % Partial Load (75%) 75.7 % Partial Load (50%) 71.2 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 80MD 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	49 kg
Product Type	3JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

