

PRODUCT-DETAILS

3GJM082310-ADH

M3JM 80MA 4

"No longer for sale" replaced by 3GJM082310-



General Information

Product ID	3GJM082310-ADH
ABB Type Designation	M3JM 80MA 4
Catalog Description	M3JM 80MA 4

Additional Information

ABB Type Designation	M3JM 80MA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
EX-Protection	Exd

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	0.55 kW	1421 r/min	0.86 A	0.730	76.60 %	3.70 N-m	4.70
D	--	50 Hz	400 V	0.55 kW	1421 r/min	1.49 A	0.730	76.90 %	3.70 N-m	4.70
D	--	50 Hz	415 V	0.55 kW	1427 r/min	1.50 A	0.710	76.70 %	3.68 N-m	4.90

Gross Weight

43 kg

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1
	Full Load (100%) 76.6 %
	Partial Load (75%) 76.9 %
	Partial Load (50%) 74.1 %
IM Class	IMB3 IM1001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 80MA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	40 kg
Product Type	3JM2__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Replacement Product ID (NEW)	3GJM082310-ADJ
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

