

PRODUCT-DETAILS

3GJM082340-ASJ

No Description Available



General Information

Product ID	3GJM082340-ASJ
ABB Type Designation	M3JM 80MD 4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 80MD 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.75 kW	1430 r/min	1.82 A	0.730	79.60 %	5.00 N·m	6.50
D	--	50 Hz	230 V	0.75 kW	1430 r/min	3.17 A	0.730	79.60 %	5.00 N·m	6.50
Y	--	60 Hz	460 V	0.75 kW	1740 r/min	1.64 A	0.690	79.90 %	4.12 N·m	6.10

Gross Weight	53 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 79.6 % Partial Load (75%) 79.6 % Partial Load (50%) 76.6 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 79.9 % Partial Load (75%) 79.0 % Partial Load (50%) 75.3 %
IM Class	IMB3 IM1001
IP Class	IP66
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	50 kg
Product Type	3JM0__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Replaced Product ID (OLD)	3GJM082320-ASH
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

