

PRODUCT-DETAILS

3GJM083310-BSK

No Description Available



General Information

Product ID	3GJM083310-BSK
ABB Type Designation	M3JM 80MA 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 80MA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exd
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.25 kW	937 r/min	0.76 A	0.640	73.30 %	2.52 N·m	2.60
D	--	50 Hz	230 V	0.25 kW	937 r/min	1.33 A	0.640	73.30 %	2.52 N·m	2.60
Y	--	50 Hz	380 V	0.25 kW	929 r/min	0.75 A	0.680	73.60 %	2.52 N·m	2.50
D	--	50 Hz	220 V	0.25 kW	929 r/min	1.31 A	0.680	73.60 %	2.52 N·m	2.50
Y	--	50 Hz	415 V	0.25 kW	941 r/min	0.79 A	0.600	72.60 %	2.52 N·m	2.60
Y	--	60 Hz	460 V	0.25 kW	1143 r/min	0.68 A	0.600	75.40 %	2.06 N·m	3.10

Gross Weight 48 kg

IC Class IC411

IE Class Data (50 Hz) IE Class IE3
Full Load (100%) 72.6 %
Partial Load (75%) 70.7 %
Partial Load (50%) 65.0 %

IE Class Data (60 Hz) IE Class IE3
Full Load (100%) 75.4 %
Partial Load (75%) 73.5 %
Partial Load (50%) 68.1 %

IM Class IMB5 IM3001

IP Class IP66

Insulation Class ICLF

Made To Order No

Minimum Order Quantity 1 piece

Number of Poles (High) 6

Order Multiple 1 piece

Package Level 1 Units 0 carton

Product Name 3-Phase squirrel cage motor

Product Net Weight 45 kg

Product Type 3JM3__M3JM_IE3_Group_I_Flameproof_Expd_mining_motor

Quote Only No

Selling Unit of Measure piece

Temperature Class Default --

Terminator Box Location D-End top

Two Speed Motor No

UNSPSC 26101100

Voltage Code S

WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

