

PRODUCT-DETAILS

3GJM083310-CDJ

No Description Available



General Information

Product ID	3GJM083310-CDJ
ABB Type Designation	M3JM 80MA 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 80MA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	0.37 kW	923 r/min	0.60 A	0.730	67.60 %	3.82 N·m	4.40
D	--	50 Hz	400 V	0.37 kW	923 r/min	1.04 A	0.730	67.60 %	3.82 N·m	4.40
D	--	60 Hz	460 V	0.37 kW	1136 r/min	0.93 A	0.680	64.00 %	3.11 N·m	5.10

Gross Weight	48 kg
--------------	-------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 67.6 % Partial Load (75%) 67.5 % Partial Load (50%) 62.6 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 64.0 % Partial Load (75%) 62.0 % Partial Load (50%) 54.9 %
IM Class	IMB14 IM3601
IP Class	IP66
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GJM083310-BDJ
Product Name	3-Phase squirrel cage motor
Product Net Weight	45 kg
Product Type	3JM0__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Replaced Product ID (OLD)	3GJM083310-CDH
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

