

PRODUCT-DETAILS

3GJM084310-BSJ

No Description Available



General Information

Product ID	3GJM084310-BSJ
ABB Type Designation	M3JM 80MA 8
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 80MA 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.18 kW	680 r/min	0.70 A	0.610	45.90 %	2.52 N·m	3.00
D	--	50 Hz	230 V	0.18 kW	680 r/min	1.21 A	0.610	45.90 %	2.52 N·m	3.00
Y	--	60 Hz	460 V	0.18 kW	845 r/min	0.65 A	0.540	46.00 %	2.03 N·m	3.40

Gross Weight	49 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 45.9 % Partial Load (75%) 45.4 % Partial Load (50%) 38.6 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 46.0 % Partial Load (75%) 43.1 % Partial Load (50%) 35.1 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	46 kg
Product Type	3JM0__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Replaced Product ID (OLD)	3GJM084310-BSH
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

