

PRODUCT-DETAILS

3GJM084320-BDJ

No Description Available



General Information

Product ID	3GJM084320-BDJ
ABB Type Designation	M3JM 80MB 8
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 80MB 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	0.25 kW	680 r/min	0.54 A	0.620	50.60 %	3.50 N·m	3.30
D	--	50 Hz	400 V	0.25 kW	680 r/min	0.94 A	0.620	50.60 %	3.50 N·m	3.30
D	--	60 Hz	460 V	0.25 kW	845 r/min	0.85 A	0.550	52.00 %	2.85 N·m	3.50

Gross Weight	50 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE2
	Full Load (100%) 50.6 %
	Partial Load (75%) 51.0 %
	Partial Load (50%) 46.0 %
IE Class Data (60 Hz)	IE Class IE2
	Full Load (100%) 52.0 %
	Partial Load (75%) 50.2 %
	Partial Load (50%) 42.8 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	47 kg
Product Type	3JM0__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Replaced Product ID (OLD)	3GJM084320-BDH
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

