

PRODUCT-DETAILS

3GJM091530-CDK

No Description Available



General Information

Product ID	3GJM091530-CDK
ABB Type Designation	M3JM 90LC 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 90LC 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	2.20 kW	2900 r/min	2.30 A	0.890	87.60 %	7.27 N·m	9.10
D	--	50 Hz	400 V	2.20 kW	2900 r/min	4.00 A	0.890	87.60 %	7.27 N·m	9.10
Y	--	50 Hz	660 V	2.20 kW	2883 r/min	2.40 A	0.900	86.80 %	7.27 N·m	6.90
D	--	50 Hz	380 V	2.20 kW	2883 r/min	4.20 A	0.900	86.80 %	7.27 N·m	6.90
D	--	50 Hz	415 V	2.20 kW	2908 r/min	3.90 A	0.890	87.90 %	7.27 N·m	8.40
D	--	60 Hz	460 V	2.20 kW	3513 r/min	3.60 A	0.890	87.10 %	6.00 N·m	10.60

Gross Weight	67 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 86.8 % Partial Load (75%) 87.8 % Partial Load (50%) 87.3 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 87.1 % Partial Load (75%) 86.6 % Partial Load (50%) 84.3 %
IM Class	IMB14 IM3601
IP Class	IP66
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GJM091530-BDK
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	64 kg
Product Type	3JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

