

PRODUCT-DETAILS

3GJM093560-ASK

No Description Available



General Information

Product ID	3GJM093560-ASK
ABB Type Designation	M3JM 90LF 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 90LF 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	1.10 kW	944 r/min	2.62 A	0.750	81.00 %	11.10 N·m	4.70
D	--	50 Hz	230 V	1.10 kW	944 r/min	4.50 A	0.750	81.00 %	11.10 N·m	4.70
Y	--	50 Hz	380 V	1.10 kW	936 r/min	2.70 A	0.770	81.00 %	11.20 N·m	4.30
D	--	50 Hz	220 V	1.10 kW	936 r/min	4.66 A	0.770	81.00 %	11.20 N·m	4.30
Y	--	50 Hz	415 V	1.10 kW	949 r/min	2.50 A	0.730	81.00 %	11.10 N·m	5.00

Gross Weight	65 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 81.0 % Partial Load (75%) 81.7 % Partial Load (50%) 80.1 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 75.0 % Partial Load (75%) 76.2 % Partial Load (50%) 74.4 %
IM Class	IMB3 IM1001
IP Class	IP66
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	62 kg
Product Type	3JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	--
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

