

PRODUCT-DETAILS

3GJM094010-ASH

M3JM 90SLA 8

"No longer for sale" replaced by 3GJM094020-



General Information

Product ID	3GJM094010-ASH
ABB Type Designation	M3JM 90SLA 8
Catalog Description	M3JM 90SLA 8

Additional Information

ABB Type Designation	M3JM 90SLA 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
EX-Protection	Exd

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.37 kW	697 r/min	1.33 A	0.630	65.50 %	5.10 N·m	3.00
D	--	50 Hz	230 V	0.37 kW	697 r/min	2.32 A	0.630	65.50 %	5.10 N·m	3.00
Y	--	50 Hz	415 V	0.37 kW	702 r/min	1.33 A	0.630	65.50 %	5.00 N·m	3.10

Gross Weight	55 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2

	Full Load (100%) 65.5 % Partial Load (75%) 63.7 % Partial Load (50%) 57.6 %
IM Class	IMB3 IM1001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 90SLA 8
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	52 kg
Product Type	3JM2__M3JM_IE2_Group_I_Flameproof_Ext_mining_motor
Quote Only	No
Replacement Product ID (NEW)	3GJM094020-ASJ
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

