

PRODUCT-DETAILS

3GJM094030-CSJ

No Description Available



General Information

Product ID	3GJM094030-CSJ
ABB Type Designation	M3JM 90SLC 8
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 90SLC 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.55 kW	673 r/min	2.08 A	0.610	61.70 %	7.80 N·m	2.60
D	--	50 Hz	230 V	0.55 kW	673 r/min	3.61 A	0.610	61.70 %	7.80 N·m	2.60
Y	--	60 Hz	460 V	0.55 kW	841 r/min	1.83 A	0.540	62.00 %	6.24 N·m	3.10

Gross Weight	60 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE2
	Full Load (100%) 61.7 %
	Partial Load (75%) 63.6 %
	Partial Load (50%) 59.8 %
IE Class Data (60 Hz)	IE Class IE2
	Full Load (100%) 62.0 %
	Partial Load (75%) 61.4 %
	Partial Load (50%) 55.3 %
IM Class	IMB14 IM3601
IP Class	IP66
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GJM094030-BSJ
Product Name	3-Phase squirrel cage motor
Product Net Weight	57 kg
Product Type	3JM0__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Replaced Product ID (OLD)	3GJM094030-CSH
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

