

PRODUCT-DETAILS

3GJM102820-ADK

No Description Available



General Information

Product ID	3GJM102820-ADK
ABB Type Designation	M3JM 100LKB 4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 100LKB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	3.00 kW	1452 r/min	3.30 A	0.830	87.70 %	19.70 N-m	7.50
D	--	50 Hz	400 V	3.00 kW	1452 r/min	5.80 A	0.830	87.70 %	19.70 N-m	7.50
Y	--	50 Hz	660 V	3.00 kW	1445 r/min	3.50 A	0.840	87.70 %	19.70 N-m	6.70
D	--	50 Hz	380 V	3.00 kW	1445 r/min	6.10 A	0.840	87.70 %	19.70 N-m	6.70
D	--	50 Hz	415 V	3.00 kW	1456 r/min	5.60 A	0.820	87.70 %	19.70 N-m	8.00
D	--	60 Hz	460 V	3.00 kW	1757 r/min	5.10 A	0.820	89.50 %	16.30 N-m	9.80

Gross Weight	85 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 87.7 % Partial Load (75%) 88.7 % Partial Load (50%) 88.4 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 89.5 % Partial Load (75%) 89.6 % Partial Load (50%) 88.2 %
IM Class	IMB3 IM1001
IP Class	IP66
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	80 kg
Product Type	3JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

