

PRODUCT-DETAILS

# 3GJM102820-BDK

No Description Available



## General Information

|                      |                          |
|----------------------|--------------------------|
| Product ID           | 3GJM102820-BDK           |
| ABB Type Designation | M3JM 100LKB 4            |
| Catalog Description  | No Description Available |

## Additional Information

|                       |               |
|-----------------------|---------------|
| ABB Type Designation  | M3JM 100LKB 4 |
| Altitude              | 1000 m        |
| Ambient Temperature   | 40 °C         |
| Bearing               | 6206-2Z/C3    |
| Bearing NDE           | 6205-2Z/C3    |
| Country of Origin     | Finland (FI)  |
| Customs Tariff Number | 85015220      |
| Direction of Rotation | Both sides    |
| EX-Protection         | Exdb          |
| Electrical Data       |               |

| Conn | Temp Class | Freq  | Voltage | Power   | Speed      | Current | Power Factor | Efficiency | Torque    | IS/IN |
|------|------------|-------|---------|---------|------------|---------|--------------|------------|-----------|-------|
| Y    | --         | 50 Hz | 690 V   | 3.00 kW | 1452 r/min | 3.30 A  | 0.830        | 87.70 %    | 19.70 N-m | 7.50  |
| D    | --         | 50 Hz | 400 V   | 3.00 kW | 1452 r/min | 5.80 A  | 0.830        | 87.70 %    | 19.70 N-m | 7.50  |
| Y    | --         | 50 Hz | 660 V   | 3.00 kW | 1445 r/min | 3.50 A  | 0.840        | 87.70 %    | 19.70 N-m | 6.70  |
| D    | --         | 50 Hz | 380 V   | 3.00 kW | 1445 r/min | 6.10 A  | 0.840        | 87.70 %    | 19.70 N-m | 6.70  |
| D    | --         | 50 Hz | 415 V   | 3.00 kW | 1456 r/min | 5.60 A  | 0.820        | 87.70 %    | 19.70 N-m | 8.00  |
| D    | --         | 60 Hz | 460 V   | 3.00 kW | 1757 r/min | 5.10 A  | 0.820        | 89.50 %    | 16.30 N-m | 9.80  |

|                           |                                                                                                   |
|---------------------------|---------------------------------------------------------------------------------------------------|
| Gross Weight              | 85 kg                                                                                             |
| IC Class                  | IC411                                                                                             |
| IE Class Data (50 Hz)     | IE Class IE3<br>Full Load (100%) 87.7 %<br>Partial Load (75%) 88.7 %<br>Partial Load (50%) 88.4 % |
| IE Class Data (60 Hz)     | IE Class IE3<br>Full Load (100%) 89.5 %<br>Partial Load (75%) 89.6 %<br>Partial Load (50%) 88.2 % |
| IM Class                  | IMB5 IM3001                                                                                       |
| IP Class                  | IP66                                                                                              |
| Insulation Class          | ICLF                                                                                              |
| Made To Order             | No                                                                                                |
| Minimum Order Quantity    | 1 piece                                                                                           |
| Number of Poles (High)    | 4                                                                                                 |
| Order Multiple            | 1 piece                                                                                           |
| Package Level 1 Units     | 0 carton                                                                                          |
| Product Name              | 3-Phase squirrel cage motor                                                                       |
| Product Net Weight        | 80 kg                                                                                             |
| Product Type              | 3JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor                                                |
| Quote Only                | No                                                                                                |
| Selling Unit of Measure   | piece                                                                                             |
| Temperature Class Default | --                                                                                                |
| Terminator Box Location   | D-End top                                                                                         |
| Two Speed Motor           | No                                                                                                |
| Type of Duty              | S1                                                                                                |
| UNSPSC                    | 26101100                                                                                          |
| Voltage Code              | D                                                                                                 |
| WEEE Category             | 5. Small Equipment (No External Dimension More Than 50 cm)                                        |

## Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

