

PRODUCT-DETAILS

3GJM111370-AFK

M3JM 112MG 2



General Information

Product ID	3GJM111370-AFK
ABB Type Designation	M3JM 112MG 2
Catalog Description	M3JM 112MG 2

Additional Information

ABB Type Designation	M3JM 112MG 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	500 V	4.00 kW	2870 r/min	5.60 A	0.930	88.10 %	13.30 N·m	7.30
Y	--	60 Hz	575 V	4.00 kW	3489 r/min	4.80 A	0.930	89.40 %	10.90 N·m	8.80

Gross Weight	91 kg
--------------	-------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 88.1 % Partial Load (75%) 89.7 % Partial Load (50%) 90.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 89.4 % Partial Load (75%) 89.9 % Partial Load (50%) 90.5 %
IM Class	IMB3 IM1001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 112MG 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	86 kg
Product Type	3JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	F
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

