

PRODUCT-DETAILS

3GJM112370-ADK

No Description Available



General Information

Product ID	3GJM112370-ADK
ABB Type Designation	M3JM 112MG 4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 112MG 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	4.00 kW	1454 r/min	5.00 A	0.750	88.70 %	26.30 N·m	7.50
D	--	50 Hz	400 V	4.00 kW	1454 r/min	8.70 A	0.750	88.60 %	26.30 N·m	7.50
Y	--	50 Hz	660 V	4.00 kW	1446 r/min	5.20 A	0.770	88.60 %	26.36 N·m	6.80
D	--	50 Hz	380 V	4.00 kW	1446 r/min	8.90 A	0.770	88.60 %	26.40 N·m	6.80
D	--	50 Hz	415 V	4.00 kW	1457 r/min	8.60 A	0.730	88.90 %	26.16 N·m	7.90
D	--	60 Hz	460 V	4.00 kW	1760 r/min	7.60 A	0.740	89.80 %	21.70 N·m	8.80

Gross Weight	87 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 88.6 % Partial Load (75%) 89.1 % Partial Load (50%) 88.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 89.8 % Partial Load (75%) 89.7 % Partial Load (50%) 88.3 %
IM Class	IMB3 IM1001
IP Class	IP66
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	82 kg
Product Type	3JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

