

PRODUCT-DETAILS

3GJM133230-CSH

M3JM 132SMC 6

"No longer for sale" replaced by 3GJM133230-



General Information

Product ID	3GJM133230-CSH
ABB Type Designation	M3JM 132SMC 6
Catalog Description	M3JM 132SMC 6

Additional Information

ABB Type Designation	M3JM 132SMC 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
EX-Protection	Exd

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	4.00 kW	967 r/min	9.26 A	0.750	85.70 %	39.50 N·m	6.40
D	--	50 Hz	230 V	4.00 kW	967 r/min	16.10 A	0.750	85.70 %	39.50 N·m	6.30
Y	--	50 Hz	415 V	4.00 kW	970 r/min	9.30 A	0.730	85.70 %	39.40 N·m	6.60

Gross Weight	116 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2

	Full Load (100%) 85.7 % Partial Load (75%) 85.1 % Partial Load (50%) 82.6 %
IM Class	IMB14 IM3601
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 132SMC 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GJM081310-BDH
Product Name	3-Phase squirrel cage motor
Product Net Weight	111 kg
Product Type	3JM2__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Replacement Product ID (NEW)	3GJM133230-CSJ
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

