

PRODUCT-DETAILS

3GJM133240-ADK

No Description Available



General Information

Product ID	3GJM133240-ADK
ABB Type Designation	M3JM 132SMD 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 132SMD 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	3.00 kW	977 r/min	4.00 A	0.690	85.60 %	29.00 N-m	5.90
D	--	50 Hz	400 V	3.00 kW	977 r/min	6.90 A	0.690	85.60 %	29.00 N-m	5.90
Y	--	50 Hz	660 V	3.00 kW	973 r/min	4.10 A	0.710	88.50 %	29.00 N-m	5.30
D	--	50 Hz	380 V	3.00 kW	973 r/min	7.10 A	0.710	85.60 %	29.00 N-m	5.30
D	--	50 Hz	415 V	3.00 kW	977 r/min	6.90 A	0.670	85.60 %	29.00 N-m	6.20
D	--	60 Hz	460 V	3.00 kW	1179 r/min	6.10 A	0.680	89.50 %	24.00 N-m	6.50

Gross Weight 128 kg

IC Class IC411

IE Class Data (50 Hz) IE Class IE3
Full Load (100%) 85.6 %
Partial Load (75%) 85.6 %
Partial Load (50%) 83.6 %

IE Class Data (60 Hz) IE Class IE3
Full Load (100%) 89.5 %
Partial Load (75%) 89.0 %
Partial Load (50%) 87.0 %

IM Class IMB3 IM1001

IP Class IP66

Insulation Class ICLF

Made To Order No

Minimum Order Quantity 1 piece

Number of Poles (High) 6

Order Multiple 1 piece

Package Level 1 Units 0 carton

Product Name 3-Phase squirrel cage motor

Product Net Weight 123 kg

Product Type 3JM3__M3JM_IE3_Group_I_Flameproof_Exp_mining_motor

Quote Only No

Selling Unit of Measure piece

Temperature Class Default --

Terminator Box Location D-End top

Two Speed Motor No

Type of Duty S1

UNSPSC 26101100

Voltage Code D

WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

