

PRODUCT-DETAILS

3GJM133260-AEJ

No Description Available



General Information

Product ID	3GJM133260-AEJ
ABB Type Designation	M3JM 132SMF 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 132SMF 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	500 V	5.50 kW	965 r/min	10.20 A	0.710	86.00 %	54.40 N-m	5.10
D	--	60 Hz	575 V	5.50 kW	1165 r/min	9.10 A	0.700	85.50 %	44.97 N-m	5.70

Gross Weight	129 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2

	Full Load (100%) 86.0 % Partial Load (75%) 86.4 % Partial Load (50%) 85.3 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 85.5 % Partial Load (75%) 84.8 % Partial Load (50%) 82.2 %
IM Class	IMB3 IM1001
IP Class	IP66
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	124 kg
Product Type	3JM0__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Replaced Product ID (OLD)	3GJM133240-AEH
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	E
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

