

PRODUCT-DETAILS

3GJM133270-CSK

No Description Available



General Information

Product ID	3GJM133270-CSK
ABB Type Designation	M3JM 132SMG 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3JM 132SMG 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	4.00 kW	974 r/min	9.30 A	0.690	86.80 %	38.70 N-m	5.60
D	--	50 Hz	230 V	4.00 kW	974 r/min	16.20 A	0.690	86.80 %	38.70 N-m	5.60
Y	--	50 Hz	380 V	4.00 kW	970 r/min	9.60 A	0.710	86.80 %	38.70 N-m	5.10
D	--	50 Hz	220 V	4.00 kW	970 r/min	16.50 A	0.710	86.80 %	38.70 N-m	5.10
Y	--	50 Hz	415 V	4.00 kW	976 r/min	9.20 A	0.670	86.80 %	38.70 N-m	5.90
Y	--	60 Hz	460 V	4.00 kW	1176 r/min	8.10 A	0.680	89.50 %	32.00 N-m	6.30

Gross Weight	128 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 86.8 % Partial Load (75%) 87.0 % Partial Load (50%) 85.9 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 89.5 % Partial Load (75%) 89.3 % Partial Load (50%) 87.8 %
IM Class	IMB14 IM3601
IP Class	IP66
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GJM133270-BSK
Product Name	3-Phase squirrel cage motor
Product Net Weight	123 kg
Product Type	3JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

