

PRODUCT-DETAILS

3GJM161430-ASL

M3JM 160MLC 2



General Information

Product ID	3GJM161430-ASL
ABB Type Designation	M3JM 160MLC 2
Catalog Description	M3JM 160MLC 2

Additional Information

ABB Type Designation	M3JM 160MLC 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309/C3
Bearing NDE	6309/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	18.50 kW	2949 r/min	32.00 A	0.900	92.40 %	59.81 N·m	9.00
D	--	50 Hz	230 V	18.50 kW	2949 r/min	55.50 A	0.900	92.40 %	59.81 N·m	9.00
Y	--	50 Hz	415 V	18.50 kW	2952 r/min	31.10 A	0.890	92.40 %	59.74 N·m	9.60
Y	--	60 Hz	440 V	18.50 kW	3551 r/min	28.80 A	0.900	91.70 %	49.70 N·m	9.60
Y	--	60 Hz	460 V	18.50 kW	3555 r/min	27.90 A	0.890	91.70 %	49.64 N·m	10.50

Gross Weight	264 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 92.4 % Partial Load (75%) 92.9 % Partial Load (50%) 92.3 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 91.7 % Partial Load (75%) 91.9 % Partial Load (50%) 90.7 %
IM Class	IMB3 IM1001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 160MLC 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	254 kg
Product Type	5JM3__M3JM_IE3_Group_I_Flameproof_Expd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

