

PRODUCT-DETAILS

# 3GJM163410-ASK

## M3JM 160MLA 6



### General Information

|                      |                |
|----------------------|----------------|
| Product ID           | 3GJM163410-ASK |
| ABB Type Designation | M3JM 160MLA 6  |
| Catalog Description  | M3JM 160MLA 6  |

### Additional Information

|                       |               |
|-----------------------|---------------|
| ABB Type Designation  | M3JM 160MLA 6 |
| Altitude              | 1000 m        |
| Ambient Temperature   | 40 °C         |
| Bearing               | 6309/C3       |
| Bearing NDE           | 6309/C3       |
| Country of Origin     | Finland (FI)  |
| Customs Tariff Number | 85015220      |
| EX-Protection         | Exdb          |
| Electrical Data       |               |

| Conn | Temp Class | Freq  | Voltage | Power   | Speed      | Current | Power Factor | Efficiency | Torque    | IS/IN |
|------|------------|-------|---------|---------|------------|---------|--------------|------------|-----------|-------|
| Y    | --         | 50 Hz | 400 V   | 7.50 kW | 980 r/min  | 15.20 A | 0.780        | 90.80 %    | 73.00 N-m | 7.90  |
| D    | --         | 50 Hz | 230 V   | 7.50 kW | 980 r/min  | 26.60 A | 0.780        | 90.80 %    | 73.00 N-m | 7.90  |
| Y    | --         | 50 Hz | 380 V   | 7.50 kW | 977 r/min  | 15.70 A | 0.800        | 90.40 %    | 73.00 N-m | 7.20  |
| D    | --         | 50 Hz | 220 V   | 7.50 kW | 977 r/min  | 27.30 A | 0.800        | 90.40 %    | 73.00 N-m | 7.20  |
| Y    | --         | 50 Hz | 415 V   | 7.50 kW | 981 r/min  | 14.80 A | 0.770        | 91.00 %    | 73.00 N-m | 8.40  |
| Y    | --         | 60 Hz | 460 V   | 7.50 kW | 1182 r/min | 13.50 A | 0.760        | 91.40 %    | 60.50 N-m | 8.60  |

|                           |                                                                                                   |
|---------------------------|---------------------------------------------------------------------------------------------------|
| Gross Weight              | 261 kg                                                                                            |
| IC Class                  | IC411                                                                                             |
| IE Class Data (50 Hz)     | IE Class IE3<br>Full Load (100%) 90.4 %<br>Partial Load (75%) 91.4 %<br>Partial Load (50%) 91.2 % |
| IE Class Data (60 Hz)     | IE Class IE3<br>Full Load (100%) 91.4 %<br>Partial Load (75%) 91.5 %<br>Partial Load (50%) 90.3 % |
| IM Class                  | IMB3 IM1001                                                                                       |
| IP Class                  | IP66                                                                                              |
| Insulation Class          | ICLF                                                                                              |
| Invoice Description       | M3JM 160MLA 6                                                                                     |
| Made To Order             | No                                                                                                |
| Minimum Order Quantity    | 1 piece                                                                                           |
| Number of Poles (High)    | 6                                                                                                 |
| Order Multiple            | 1 piece                                                                                           |
| Package Level 1 Units     | 0 pallet (lift)                                                                                   |
| Product Name              | 3-Phase squirrel cage motor                                                                       |
| Product Net Weight        | 251 kg                                                                                            |
| Product Type              | 3JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor                                                |
| Quote Only                | No                                                                                                |
| Selling Unit of Measure   | piece                                                                                             |
| Temperature Class Default | --                                                                                                |
| Terminator Box Location   | Top                                                                                               |
| Two Speed Motor           | No                                                                                                |
| Type of Duty              | S1                                                                                                |
| UNSPSC                    | 26101100                                                                                          |
| Voltage Code              | S                                                                                                 |
| WEEE Category             | 4. Large Equipment (Any External Dimension More Than 50 cm)                                       |

## Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

