

PRODUCT-DETAILS

3GJM163410-BSL

M3JM 160MLA 6



General Information

Product ID	3GJM163410-BSL
ABB Type Designation	M3JM 160MLA 6
Catalog Description	M3JM 160MLA 6

Additional Information

ABB Type Designation	M3JM 160MLA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309/C3
Bearing NDE	6309/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	7.50 kW	975 r/min	15.70 A	0.770	89.10 %	73.24 N-m	5.70
D	--	50 Hz	230 V	7.50 kW	975 r/min	27.40 A	0.770	89.10 %	73.24 N-m	5.70
Y	--	50 Hz	415 V	7.50 kW	976 r/min	15.40 A	0.760	89.10 %	73.10 N-m	6.10
Y	--	60 Hz	440 V	7.50 kW	1176 r/min	14.00 A	0.780	91.00 %	60.80 N-m	6.10
Y	--	60 Hz	460 V	7.50 kW	1179 r/min	13.50 A	0.770	91.00 %	60.70 N-m	6.70

Gross Weight	243 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 89.1 % Partial Load (75%) 89.7 % Partial Load (50%) 89.4 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 91.0 % Partial Load (75%) 91.3 % Partial Load (50%) 90.6 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 160MLA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	233 kg
Product Type	5JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	--
Default	
Terminator Box Location	Top
Two Speed Motor	No
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

