

PRODUCT-DETAILS

3GJM181420-AEH

M3JM 180MLB 2



General Information

Product ID	3GJM181420-AEH
ABB Type Designation	M3JM 180MLB 2
Catalog Description	M3JM 180MLB 2

Additional Information

ABB Type Designation	M3JM 180MLB 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6310/C3
Bearing NDE	6310/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	500 V	30.00 kW	2942 r/min	41.80 A	0.900	92.50 %	97.30 N-m	7.00

Gross Weight	317 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 92.5 % Partial Load (75%) 93.2 %

	Partial Load (50%) 92.6 %
IM Class	IMB3 IM1001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 180MLB 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	307 kg
Product Type	3JM2__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

