

PRODUCT-DETAILS

3GJM182430-BSH

M3JM 180MLC 4



General Information

Product ID	3GJM182430-BSH
ABB Type Designation	M3JM 180MLC 4
Catalog Description	M3JM 180MLC 4

Additional Information

ABB Type Designation	M3JM 180MLC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6310/C3
Bearing NDE	6310/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	30.00 kW	1473 r/min	59.60 A	0.810	92.10 %	194.50 N·m	7.60
D	--	50 Hz	230 V	30.00 kW	1473 r/min	103.00 A	0.810	92.10 %	194.50 N·m	7.60
Y	--	50 Hz	415 V	30.00 kW	1468 r/min	59.50 A	0.790	92.20 %	194.20 N·m	8.00

Gross Weight	323 kg
--------------	--------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1
	Full Load (100%) 92.1 %
	Partial Load (75%) 92.4 %
	Partial Load (50%) 91.8 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 180MLC 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	313 kg
Product Type	3JM2__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	--
Default	
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

